



GOODTIME RUBBER CO., LTD.

Factory: KM32, National Road 22, An Tinh Village,
Trang Bang District, Tay Ninh Province, Vietnam

Tel: 886-4-8322568 Fax: 886-4-8331186

[Http://www.goodtimegroup.com.tw](http://www.goodtimegroup.com.tw)

E-mail: sales@mail.goodtimegroup.com.tw



GOODTIME

TIRES AND TUBES MANUFACTURER



DOT
ISO 9001

INDEX



■ ATV TIRE
P01



■ TRAILER TIRE
■ GO KART TIRE
P07~P09



■ SOLID AIR TIRE
■ FORK LIFTER TIRE
■ GOLF TIRE
P02



■ AGRICULTURAL
TRACTOR TIRE
P10~P11



■ WHEEL BARROW TIRE
■ LAWN MOWER & GARDEN TIRE
P03



■ SNOW HOG TIRE
■ ALL KINDS OF TUBES
P11



■ IMPLEMENT TIRE
P04~P05

SIZE	PLY	P.R.
20 x 10.00-9	4PR	20
21 x 7.00-10	4PR	20.5
	6PR	20.9
25 x 8.00-12	4PR	25.0
	6PR	25.0
25 x 10.00-12	4PR	25.0
	6PR	25.0
145 / 70-6	2PR	
	4PR	

■ TECHNICAL DATA
P12~P17



■ LIGHT TRUCK TIRE
P06

ATV TIRE



V-1502
20 x 10.00-9
21 x 7.00-10



V-1503
25 x 8.00-12
25 x 10.00-12



V-1505
21 x 9.00-10



V-1509
145 / 70-6



V-1511
21 x 7.00-10



V-1512
20 x 11.00-8
21 x 10.00-8
20 x 11.00-9
20 x 11.00-10



V-1513
165 / 70-10



V-1515
225 / 40-10



V-1568
19 x 7.00-8
18 x 9.50-8
25 x 8.00-12
25 x 10.00-12

SOLID AIR TIRE



V-2505

16 x 6-8 7.00-12
18 x 7-8 300-15
5.00-8 28 x 9-15
21 x 8-9 8.15-15
6.00-9 8.25-15
6.50-10 7.50-16
23 x 9-10



V-2506

6.00-9
6.50-10
7.00-12



V-5501

3.00-4



V-6602

4.10 / 3.50-6
4.80 / 4.00-8



V-6604

4.10 / 3.50-4

FORK LIFTER TIRE



V-6606

2.50-4



V-817

30 x 10-16



V-2502

5.00-8
6.00-9
6.50-10
7.00-12



V-3504

18 x 8.50-8

GOLF TIRE

WHEEL BARROW TIRE



V-5501

6 x 11 / 4 2.50-6
200 x 50 3.50-6
2.50-3 4.00-6
2.50-4 3.50-8
3.00-4 4.80 / 4.00-8
4.00-4



V-5502

260 / 165-60



V-6504

4.00-4



V-6605

3.00-4
3.00-4(260*85)
4.00-4



V-6636

4.80 / 4.00-8



V-9128W

3.50-8

LAWN MOWER & GARDEN TIRE



V-3501

18 x 8.50-8



V-3502

4.10/3.50-4 16 x 6.50-8
9 x 3.50-4 16 x 7.50-8
11 x 4.00-4 18 x 6.50-8
11 x 4.00-5 18 x 9.50-8
13 x 5.00-6 20 x 8.00-8
13 x 6.50-6 20 x 10.00-8
15 x 6.00-6



V-3503

11 x 4.00-5
13 x 5.00-6
13 x 6.50-6
15 x 6.00-6
16 x 6.50-8
18 x 8.50-8



KT-738G

4.10/3.50-4



KT-739G

9 x 3.50-4
4.10/3.50-5

IMPLEMENT TIRE



V-6511 12 1/2 x 2 1/4-8
V-6534 4.00-5
V-6536 13 x 5.00-6
V-6541 4.10 / 3.50-4
V-6542 4.10 / 3.50-4



V-6601 2.80 / 2.50-4
 4.10 / 3.50-4
 4.10 / 3.50-6
 13 x 3.00-8(3.00-8)
 4.80-8
V-6602 4.00-4
 4.10 / 3.50-4
 4.10 / 3.50-5
 4.10 / 3.50-6
 5.30 / 4.50-6
 4.80-8
V-6603 4.10 / 3.50-4
 4.10 / 3.50-6
V-6604 4.10 / 3.50-4
 4.10 / 3.50-5
 4.00-6
 4.10 / 3.50-6
V-6605 4.10 / 3.50-6
 4.80-8

IMPLEMENT TIRE



V-6606 2.50-4
V-6607 2.50-4
 2.50-6
 2.50-8
V-6609 3.00-4
V-6612 2.50-6
V-6631 3.00-4
 310 * 100-4
 4.80 / 4.00-8



V-6632 4.10 / 3.50-5
 4.00-6
 4.80-8
V-6633 4.10 / 3.50-4
 4.10 / 3.50-5
V-6635 200 x 50
 4.10 / 3.50-6
 13 x 3.00-8(3.00-8)
 4.80 / 4.00-8
V-6637 4.80-8

LIGHT TRUCK TIRE



V-7219
5.00-12



V-7319
5.00-12
5.50-13
6.00-13
7.00-16
7.50-16
8.25-16



V-7512
5.00-12



V-7518
5.50-13 6.50-16
6.00-14 7.00-16
6.50-15 7.50-16
7.00-15 8.25-16
7.50-15



V-7519
7.00-16
7.50-16



V-7529
6.00-14
8.25-16



V-7557
5.50-13
6.00-14
6.50-14
6.50-15
7.00-16
7.50-16
8.25-16



V-7711
5.00-12
7.50-16



TRAILER TIRE



V-6509
6.00-9



V-6606
4.80-8



V-6631
5.00-8
6.00-9



V-6632
4.00-10



V-6638
4.80-8



V-7515
4.50-10



V-7566
4.80-8



V-7582
4.80-8
4.00-10
4.50-10
5.00-10



V-7711
5.00-10



V-7761
6.00-9



TRAILER TIRE



V-7762
5.00-10



V-7763
5.00-8



V-7768
4.50-10



V-9128
3.50-8



KT-701
4.80-8
5.70-8
4.80-12
5.30-12



KT-705
16.5 * 6.5-8
18.5 * 8.5-8
20.5 * 8.0-10



KT-715
4.00-10
4.50-10
5.00-10



KT-729
ST175 / 80D13



KT-747
145-10



KT-7166
195 / 50B10



GO KART TIRE



KT-735
10.5 * 4.50-6
11 * 6.00-6
12 * 8.00-6



KT-736
12 * 4.00-5



KT-738
4.10 / 3.50-4



KT-739
9 * 3.50-4
10 * 4.50-5
11 * 6.00-5
11 * 7.10-5
4.10 / 3.50-5
13 * 5.00-6



AGRICULTURAL TRACTOR TIRE



V-8501

13 * 5.00-6
4.80 / 4.00-8
16 x 6.50-8
5.00-10
6.5 / 80-15

V-8502

3.00-4 4.00-8
4.00-4 4.80-8
3.50-6 5.50-16
4.00-6 6.00-16
3.50-8

V-8504

3.50-6

V-8506

19 x 8.00-10

V-8508

10-16.5



V-8509

5.00-12
5.50-13
6.00-14

V-8558

16 x 6.50-8

V-8803

3.00-4 4.00-10
4.00-4 4.50-10
3.50-6 5.00-10
13 x 5.00-6 5.00-12
3.50-8 6.00-12
4.00-8

V-8813

4.00-4
5.00-8
5.00-10

V-8814

3.50-5

AGRICULTURAL TRACTOR TIRE



V-8816

4.00-8
4.00-10

V-8817

16 x 6.50-8

V-8818

4.00-7

V-8819

3.50-7

V-8911

10-16.5
12-16.5

SNOW HOG TIRE

ALL KINDS OF TUBES



V-8509

5.00-12
5.50-13
6.00-14

V-8558

16 x 6.50-8

V-8803

3.00-4 4.00-10
4.00-4 4.50-10
3.50-6 5.00-10
13 x 5.00-6 5.00-12
3.50-8 6.00-12
4.00-8

V-8813

4.00-4
5.00-8
5.00-10

V-8814

3.50-5

V-8505

4.10-6
13 x 5.00-6
15 * 5.00-6
4.00-8
4.80-8
16 x 6.50-8



Atv Tire

PATTERN	SIZE	P.R	O.D	S.W	INFLATION		MAXLOAD		R.W.INCHES	
		PLY	In / mm	In / mm	P.S.I	BAR	LBS	KGS	Width	Inches
V-1502	20 x 10.00-9	4PR	20.0 / 508	10.0 / 254	5	0.4	260	118	8.00	9
V-1502	21 x 7.00-10	4PR	20.9 / 530	6.9 / 174	5	0.4	205	93	5.50	10
		6PR	20.9 / 530	6.9 / 174	7	0.5	235	106	5.50	10
V-1503	25 x 8.00-12	4PR	25.0 / 635	8.0 / 204	5	0.4	290	132	6.50	12
		6PR	25.0 / 635	8.0 / 204	7	0.5	340	155	6.50	12
V-1503	25 x 10.00-12	4PR	25.0 / 635	10.0 / 254	5	0.4	365	165	8.00	12
		6PR	25.0 / 635	10.0 / 254	7	0.5	420	190	8.00	12
V-1505	21x9.00-10	6PR	20.04 / 509	9.06 / 230	7	0.5	276	125	7.00	10
V-1509	145 / 70-6	2PR	14.2 / 354	5.8 / 148	5	0.4	128	58	5.00	6
		4PR	14.2 / 354	5.8 / 148	14	1.0	155	70	5.00	6
V-1511	21 x 7.00-10	4PR	21.0 / 533	7.0 / 177	5	0.4	205	93	5.50	10
		6PR	21.0 / 533	7.0 / 177	7	0.5	235	106	5.50	10
V-1512	20 x 11.00-8	4PR	20.0 / 508	11.1 / 281	5	0.4	290	132	9.00	8
V-1512	21 x 10.00-8	4PR	20.2 / 514	10.0 / 254	5	0.4	240	109	8.00	8
		4PR	20.0 / 508	11.1 / 281	5	0.4	290	132	9.00	9
V-1512	20 x 11.00-9	6PR	20.0 / 508	11.1 / 281	7	0.5	340	155	9.00	9
		4PR	20.0 / 508	11.1 / 281	5	0.4	280	128	8.50	10
V-1512	20 x 11.00-10	6PR	20.0 / 508	11.1 / 281	7	0.5	330	150	8.50	10
V-1513	165 / 70-10	4PR	19.7 / 499	7.4 / 187	24	1.7	216	98	6.00	10
V-1515	225 / 40-10	4PR	19.0 / 483	10.1 / 256	24	1.7	216	98	8.00	10
V-1568	19 x 7.00-8	2PR	19.1 / 486	7.1 / 181	5	0.4	193	87	5.375	8
		4PR	19.1 / 486	7.1 / 181	5	0.4	240	109	5.375	8
V-1568	18 x 9.50-8	2PR	18.3 / 464	9.4 / 238	5	0.4	192	87	7.00	8
		4PR	18.3 / 464	9.4 / 238	5	0.4	240	109	7.00	8
V-1568	25 x 8.00-12	4PR	25.0 / 635	8.0 / 204	5	0.4	290	132	6.50	12
		6PR	25.0 / 635	8.0 / 204	7	0.5	340	155	6.50	12
		8PR	25.0 / 635	8.0 / 204	7	0.5	395	180	6.50	12
V-1568	25 x 10.00-12	4PR	25.0 / 635	10.0 / 254	5	0.4	365	165	8.00	12
		6PR	25.0 / 635	10.0 / 254	7	0.5	420	190	8.00	12
		8PR	25.0 / 635	10.0 / 254	7	0.5	480	218	8.00	12

Solid Air Tire, Fork Lifter Tire, Golf Tire

PATTERN	SIZE	P.R	O.D	S.W	INFLATION		MAXLOAD		R.W.INCHES	
		PLY	In / mm	In / mm	P.S.I	BAR	LBS	KGS	Width	Inches
V-2505	16 x 6-8		16.26 / 413	5.79 / 147					4.33R	8
V-2505	18 x 7-8		17.40 / 442	6.30 / 160					4.33R	8
V-2505	5.00-8		18.19 / 462	5.47 / 139					3.50D	8
V-2505	21 x 8-9		20.59 / 523	7.28 / 185					4.00E	9
V-2505	6.00-9		21.18 / 538	6.69 / 170					4.00E	9
V-2505	6.50-10		23.15 / 588	7.32 / 186					5.00F	10
V-2505	7.00-12		26.61 / 676	7.83 / 199					5.00S	12
V-2505	300-15		33.03 / 839	11.57 / 294					6.50	15
V-2505	28 x 9-15		27.80 / 706	8.70 / 221					7.0	15
V-2505	8.15-15		27.80 / 706	8.70 / 221					7.0	15
V-2505	8.25-15		32.56 / 827	8.54 / 217					6.50	15
V-2505	7.50-16		31.26 / 794	7.68 / 195					6.00G	16
V-2506	6.00-9		21.18 / 538	6.69 / 170					4.00E	9
V-2506	6.50-10		23.15 / 588	7.32 / 186					5.00F	10
V-2506	7.00-12		26.61 / 676	7.83 / 199					5.00S	12
V-5501	3.00-4		9.96 / 253	3.11 / 79					2.1	4
V-6602	4.10 / 3.50-6		12.20 / 310	3.54 / 90					3.25	6
V-6602	4.80 / 4.00-8		15.91 / 404	4.13 / 105					3.75	8
V-6604	4.10 / 3.50-4		10.24 / 260	3.46 / 88					3.25	4
V-2502	5.00-8	8PR	18.50 / 470	5.39 / 137	100	7.00	1896	860	3.5	8
V-2502	6.00-9	10PR	21.26 / 540	6.30 / 160	100	7.00	2712	1230	4.00E	9
V-2502	6.00-9	12PR	21.26 / 540	6.30 / 160	100	7.00	2712	1230	4.00E	9
V-2502	6.50-10	10PR	23.23 / 590	6.89 / 175	100	7.00	3142	1425	5.00F	10
V-2502	7.00-12	12PR	26.61 / 676	7.48 / 190	100	7.00	4005	1815	5.00S	12
V-2502	7.00-12	14PR	26.61 / 676	7.48 / 190	100	7.00	4280	1940	5.00S	12
V-3504	18 x 8.50-8	2PR	17.3 / 440	8.4 / 213	10	0.7	515	235	7.00	8
V-3504	18 x 8.50-8	4PR	17.3 / 440	8.4 / 213	21	1.5	815	370	7.00	8
V-3504	18 x 8.50-8	6PR	17.3 / 440	8.4 / 213	33	2.3	1050	475	7.00	8

Wheel Barrow Tire

PATTERN	SIZE	P.R	O.D	S.W	INFLATION		MAXLOAD		R.W.INCHES	
		PLY	In / mm	In / mm	P.S.I	BAR	LBS	KGS	Width	Inches
V-5501	6 x 11 / 4	2PR	6.1 / 156	1.3 / 32	90	6.3	396	180	1.1	3.5
V-5501	6 x 11 / 4	4PR	6.1 / 156	1.3 / 32	90	6.3	396	180	1.1	3.5
V-5501	200 x 50	2PR	7.5 / 190	1.7 / 44	30	2.1	165	75	200 x 50	4
V-5501	200 x 50	4PR	7.5 / 190	1.7 / 44	36	2.5	271	123	200 x 50	4
V-5501	2.50-3	2PR	6.4 / 162	1.7 / 42	30	2.1	148	67	2.25	3
V-5501	2.50-3	4PR	6.4 / 162	1.7 / 42	36	2.5	183	83	2.25	3
V-5501	2.50-4	2PR	8.3 / 212	2.7 / 68	30	2.1	165	75	2.25	4
V-5501	2.50-4	4PR	8.3 / 212	2.7 / 68	36	2.5	165	75	2.25	4
V-5501	3.00-4	2PR	9.8 / 248	3.1 / 78	36	2.5	154	70	2.1	4
V-5501	3.00-4	4PR	9.8 / 248	3.1 / 78	36	2.5	154	70	2.1	4
V-5501	4.00-4	2PR	11.7 / 296	3.9 / 100	30	2.1	260	120	2.75	4
V-5501	4.00-4	4PR	11.7 / 296	3.9 / 100	36	2.5	290	130	2.75	4
V-5501	2.50-6	2PR	11.4 / 290	2.4 / 62	30	2.1	209	95	2.25	6
V-5501	2.50-6	4PR	11.4 / 290	2.4 / 62	36	2.5	242	110	2.25	6

Wheel Barrow Tire

PATTERN	SIZE	P.R	O.D	S.W	INFLATION		MAXLOAD		R.W.INCHES	
		PLY	In / mm	In / mm	P.S.I	BAR	LBS	KGS	Width	Inches
V-5501	3.50-6	2PR	12.8 / 326	3.9 / 99	30	2.1	308	140	2.50	6
V-5501	3.50-6	4PR	12.8 / 326	3.9 / 99	36	2.5	441	200	2.50	6
V-5501	4.00-6	2PR	13.5 / 343	4.2 / 106	30	2.1	330	150	2.50	6
V-5501	4.00-6	4PR	13.5 / 343	4.2 / 106	36	2.5	460	210	2.50	6
V-5501	4.00-6	6PR	13.5 / 343	4.2 / 106	50	3.5	595	270	2.50	6
V-5501	3.50-8	2PR	14.8 / 377	3.6 / 92	30	2.1	330	150	2.50	6
V-5501	3.50-8	4PR	14.8 / 377	3.6 / 92	36	2.5	400	180	2.50	6
V-5501	3.50-8	6PR	14.8 / 377	3.6 / 92	50	3.5	460	209	2.50	6
V-5501	4.80 / 4.00-8	2PR	15.7 / 399	4.1 / 103	30	2.1	365	165	3.75	8
V-5501	4.80 / 4.00-8	4PR	15.7 / 399	4.1 / 103	36	2.5	484	220	3.75	8
V-5502	260 / 165-6	4PR	10.2 / 258	2.6 / 66	50	3.5	286	130	1.25	6
V-6504	4.00-4	2PR	12.2 / 310	4.1 / 105	36	2.5	310	140	2.50	4
		4PR	12.2 / 310	4.1 / 105	40	2.8	400	180	2.50	4
V-6605	3.00-4	2PR	10.0 / 253	3.4 / 86	30	2.1	154	70	2.10	4
V-6605	3.00-4	4PR	10.0 / 253	3.4 / 86	36	2.5	243	110	2.10	4
V-6605	3.00-4(260 * 85)	2PR	9.8 / 248	3.3 / 83	30	2.1	154	70	2.10	4
V-6605	3.00-4(260 * 85)	4PR	9.8 / 243	3.3 / 83	36	2.5	243	110	2.10	4
V-6605	3.00-4	6PR	10.0 / 253	3.4 / 86	50	3.5	494	224	2.10	4
V-6605	4.00-4	2PR	12.1 / 308	4.1 / 104	30	2.1	260	120	2.50	4
V-6605	4.00-4	4PR	12.1 / 308	4.1 / 104	36	2.5	290	130	2.50	4
V-6636	4.80 / 4.00-8	4PR	15.75 / 400	4.17 / 106	36	2.5	485	220	2.50	8
V-9128W	3.50-8	2PR	15.04 / 382	3.70 / 94	22	1.5	291	132	2.50	8
		4PR	15.04 / 382	3.70 / 94	36	2.5	375	170	2.50	8

Lawn Mower & Garden Tire

PATTERN	SIZE	P.R	O.D	S.W	INFLATION		MAXLOAD		R.W.INCHES	
		PLY	In / mm	In / mm	P.S.I	BAR	LBS	KGS	Width	Inches
V-3501	18 x 8.50-8	2PR	17.4 / 442	8.4 / 213	10	0.7	515	235	7.00	8
V-3501	18 x 8.50-8	4PR	17.4 / 442	8.4 / 213	21	1.5	815	370	7.00	8
V-3501	18 x 8.50-8	6PR	17.4 / 442	8.4 / 213	36	2.5	1069	485	7.00	8
V-3502	4.10/3.50-4	2PR	10.47 / 266	3.90 / 99	20	1.4	295	135	3.25	4
V-3502	9 x 3.50-4	2PR	8.66 / 220	3.70 / 94	22	1.5	220	100	2.75	4
V-3502	11 x 4.00-4	2PR	11.50 / 292	4.17 / 106	21	1.5	220.5	100	3.25	5
V-3502	11 x 4.00-5	2PR	10.87 / 276	4.33 / 110	24	1.7	110	100	3.25	5
V-3502	11 x 4.00-5	4PR	10.87 / 276	4.33 / 110	40	2.8	310	140	3.25	5
V-3502	13 x 5.00-6	2PR	12.50 / 317	4.50 / 115	20	1.4	295	135	3.50	6
V-3502	13 x 5.00-6	4PR	12.50 / 317	4.50 / 115	36	2.5	415	190	3.50	6
V-3502	13 x 5.00-6	6PR	12.50 / 317	4.50 / 115	42	2.9	450	205	3.50	6
V-3502	13 x 6.50-6	2PR	12.80 / 324	6.1 / 156	28	1.9	460	210	5.00	6
V-3502	13 x 6.50-6	6PR	12.80 / 324	6.1 / 156	40	2.8	570	260	5.00	6
V-3502	15 x 6.00-6	2PR	14.40 / 366	6.0 / 152	14	1	365	170	4.50	6
V-3502	15 x 6.00-6	4PR	14.40 / 366	6.0 / 152	36	2.5	639	290	4.50	6
V-3502	15 x 6.00-6	6PR	14.40 / 366	6.0 / 152	42	2.9	710	322	4.50	6
V-3502	16 x 6.50-8	2PR	16.10 / 408	6.20 / 157	14	1	415	190	5.375	8
V-3502	16 x 6.50-8	4PR	16.10 / 408	6.20 / 157	36	2.5	620	280	5.375	8
V-3502	16 x 6.50-8	6PR	16.10 / 408	6.20 / 157	42	2.9	770	349	5.375	8
V-3502	16 x 7.50-8	2PR	15.83 / 402	6.57 / 167	12	0.8	485	220	5.375	8
V-3502	18 x 6.50-8	4PR	18.58 / 472	6.69 / 170	28	1.9	770	350	5.00	8
V-3502	18 x 9.50-8	2PR	18.10 / 460	9.30 / 235	12	0.8	605	320	7.00	8
V-3502	18 x 9.50-8	4PR	18.10 / 460	9.30 / 235	24	1.7	1040	470	7.00	8
V-3502	18 x 9.50-8	6PR	18.10 / 460	6.20 / 157	40	2.8	1280	580	7.00	8
V-3502	20 x 8.00-8	2PR	20.70 / 525	8.00 / 204	10	0.7	600	270	6.00	8
V-3502	20 x 8.00-8	4PR	20.70 / 525	8.00 / 204	21	1.5	950	430	6.00	8
V-3502	20 x 10.00-8	2PR	19.69 / 500	10.55 / 268	10	0.7	750	340	8.00	8
V-3502	20 x 10.00-8	4PR	19.69 / 500	10.55 / 268	22	1.5	1190	540	8.00	8
V-3502	20 x 10.00-8	6PR	19.69 / 500	10.55 / 268	36	2.5	1370	620	8.00	8
V-3503	11 x 4.00-5	2PR	10.75 / 273	4.21 / 107	22	1.5	220	100	3.00	5
V-3503	11 x 4.00-5	4PR	10.75 / 273	4.21 / 107	40	2.8	310	140	3.00	5
V-3503	13X5.00-6	2PR	12.80 / 340	4.80 / 122	25	1.4	295	135	3.50	6
V-3503	13X5.00-6	4PR	12.80 / 340	4.80 / 122	42	2.9	450	205	3.50	6
V-3503	13X6.50-6	4PR	12.83 / 326	6.50 / 165	28	1.9	460	210	5.00	6
V-3503	15X6.00-6	2PR	14.40 / 366	6.00 / 152	14	1	365	170	4.50	6
V-3503	15X6.00-6	4PR	14.40 / 366	6.00 / 152	36	2.5	639	290	4.50	6
V-3503	15X6.00-6	6PR	14.40 / 366	6.00 / 152	42	2.9	710	322	4.50	6
V-3503	16X6.50-8	2PR	16.00 / 406	6.40 / 162	14	1	415	190	5.375	8
V-3503	16X6.50-8	4PR	16.00 / 406	6.40 / 162	36	2.5	620	280	5.375	8
V-3503	16X6.50-8	6PR	16.00 / 406	6.40 / 162	42	2.9	770	349	5.375	8
V-3503	18X8.50-8	4PR	17.72 / 450	8.66 / 220	21	1.5	815	370	7.00	8
V-3503	18X8.50-8	6PR	17.72 / 450	8.66 / 220	33	2.3	1050	475	7.00	8
KT-738G	4.10 / 3.50-4	4PR	10.31 / 262	4.21 / 107	36	2.5	350	160	3.25	4
KT-739G	9 x 3.50-4	4PR	8.54 / 217	3.54 / 90	22	1.5	220	100	2.75	4
KT-739G	4.10 / 3.50-5	4PR	11.22 / 285	4.02 / 102	36	2.5	397	180	3.25	5

Implement Tire



PATTERN	SIZE	P.R	O.D	S.W	INFLATION		MAXLOAD		R.W.INCHES	
		PLY	In / mm	In / mm	P.S.I	BAR	LBS	KGS	Width	Inches
V-6542	4.10 / 3.50-4	4PR	10.6 / 268	3.7 / 94	36	2.5	352	160	3.25	4
V-6601	2.80 / 2.50-4	2PR	8.7 / 220	2.8 / 71	30	2.1	165	75	2.25	4
V-6601	2.80 / 2.50-4	4PR	8.7 / 220	2.8 / 71	36	2.5	210	95	2.25	4
V-6601	4.10 / 3.50-4	2PR	10.6 / 268	3.7 / 94	30	2.1	232	105	3.25	4
V-6601	4.10 / 3.50-4	4PR	10.6 / 268	3.7 / 94	36	2.5	352	160	3.25	4
V-6601	4.10 / 3.50-6	4PR	12.9 / 327	3.7 / 93	36	2.5	441	200	3.00	6
V-6601	13 x 3.00(3.00-8)	4PR	12.8 / 325	3.1 / 79	36	2.5	375	170	2.5	8
V-6601	4.00-8	2PR	16.4 / 417	4.5 / 114	30	2.1	410	185	3.75	8
V-6601	4.00-8	4PR	16.4 / 417	4.5 / 114	36	2.5	506	230	3.75	8
V-6601	4.00-8	6PR	16.4 / 417	4.5 / 114	50	3.5	610	275	3.75	8
V-6602	4.00-4	4PR	10.7 / 272	3.7 / 94	36	2.5	352	160	3.25	4
V-6602	4.10 / 3.50-4	2PR	10.6 / 268	3.7 / 94	30	2.1	232	105	3.25	4
V-6602	4.10 / 3.50-4	4PR	10.6 / 268	3.7 / 94	36	2.5	352	160	3.25	4
V-6602	4.10 / 3.50-4	6PR	10.6 / 268	3.7 / 94	50	3.5	473	215	3.25	4
V-6602	4.10 / 3.50-5	2PR	11.6 / 294	3.4 / 87	30	2.1	265	120	3.25	4
V-6602	4.10 / 3.50-5	4PR	11.6 / 294	3.4 / 87	36	2.5	415	190	3.25	4
V-6602	4.10 / 3.50-6	2PR	12.9 / 327	3.7 / 94	30	2.1	295	135	3.25	4
V-6602	4.10 / 3.50-6	4PR	12.9 / 327	3.7 / 94	36	2.5	460	210	3.25	4
V-6602	4.10 / 3.50-6	6PR	12.9 / 327	3.7 / 94	50	3.5	590	270	3.25	4
V-6602	5.30 / 4.50-6	2PR	14.09 / 358	4.96 / 126	17	1.2	418	190	4.25	6
V-6602	5.30 / 4.50-6	4PR	14.09 / 358	4.96 / 126	37	2.6	640	290	4.25	6
V-6602	4.80-8	4PR	16.2 / 412	4.7 / 120	36	2.5	585	265	3.75	8
V-6603	4.10 / 3.50-4	2PR	10.6 / 270	3.6 / 91	30	2.1	232	105	3.25	4
V-6603	4.10 / 3.50-4	4PR	10.6 / 270	3.6 / 91	36	2.5	352	160	3.25	4
V-6603	4.10 / 3.50-4	6PR	10.6 / 270	3.6 / 91	50	3.5	473	215	3.25	4
V-6603	4.10 / 3.50-6	2PR	12.8 / 326	3.7 / 94	30	2.1	295	135	3.25	6
V-6603	4.10 / 3.50-6	4PR	12.8 / 326	3.7 / 94	36	2.5	460	210	3.25	6
V-6603	4.10 / 3.50-6	6PR	12.8 / 326	3.7 / 94	50	3.5	530	240	3.25	6
V-6604	4.10 / 3.50-4	2PR	10.6 / 270	3.6 / 91	30	2.1	232	105	3.25	4
V-6604	4.10 / 3.50-4	4PR	10.6 / 270	3.6 / 91	36	2.5	352	160	3.25	4
V-6604	4.10 / 3.50-4	6PR	10.6 / 270	3.6 / 91	50	3.5	473	215	3.25	4
V-6604	4.10 / 3.50-5	4PR	11.6 / 294	3.4 / 87	36	2.5	415	190	3.25	5
V-6604	4.00-6	4PR	13.94 / 354	3.94 / 100	36	2.5	440	200	3.50	6
V-6604	4.10 / 3.50-6	2PR	12.8 / 325	3.8 / 97	30	2.1	295	135	3.25	6
V-6604	4.10 / 3.50-6	4PR	12.8 / 325	3.8 / 97	36	2.5	460	210	3.25	6
V-6604	4.10 / 3.50-6	6PR	12.8 / 325	3.8 / 97	50	3.5	530	240	3.25	6
V-6605	4.10 / 3.50-6	4PR	12.8 / 326	3.7 / 94	36	2.5	460	210	3.25	6
V-6605	4.80-8	4PR	16.4 / 417	4.5 / 114	36	2.5	500	230	3.75	8
V-6606	2.50-4	4PR	8.6 / 218	2.5 / 64	36	2.5	165	75	2.25	4
V-6607	2.50-4	4PR	8.6 / 218	2.5 / 64	36	2.5	165	75	2.25	4
V-6607	2.50-6	4PR	11.3 / 288	2.5 / 64	50	3.5	320	150	1.25	6
V-6607	2.50-8	4PR	11.3 / 288	2.5 / 64	36	2.5	320	150	1.25	8
V-6609	3.00-4	2PR	10.0 / 253	3.4 / 86	30	2.1	154	70	2.10	4
V-6609	3.00-4	4PR	10.0 / 253	3.4 / 86	36	2.5	243	110	2.10	4
V-6609	3.00-4	6PR	10.0 / 253	3.4 / 86	50	3.5	494	224	2.10	4
V-6612	2.50-6	2PR	11.34 / 288	2.52 / 64	30	2.1	265	120	1.25	6
V-6612	2.50-6	4PR	11.34 / 288	2.52 / 64	36	2.5	331	150	1.25	6
V-6631	3.00-4	2PR	8.9 / 225	3.4 / 87	30	2.1	154	70	2.10	4
V-6631	3.00-4	4PR	8.9 / 225	3.4 / 87	36	2.5	243	110	2.10	4
V-6631	3.00-4	6PR	8.9 / 225	3.4 / 87	50	3.5	494	224	2.10	4
V-6631	310 x 100-4	4PR	9.8 / 250	3.1 / 80	36	2.5	342	155	3.00	4
V-6631	4.80 / 4.00-8	2PR	15.9 / 403	4.1 / 103	30	2.1	365	165	3.75	8
V-6631	4.80 / 4.00-8	4PR	15.9 / 403	4.1 / 103	36	2.5	484	220	3.75	8
V-6632	4.10 / 3.50-5	4PR	11.6 / 294	3.4 / 87	36	2.5	415	190	3.25	5
V-6632	4.00-6	4PR	14.0 / 357	4.3 / 109	36	2.5	397	180	2.50	6
V-6632	4.80-8	4PR	16.4 / 417	4.5 / 114	36	2.5	506	230	3.75	8
V-6632	4.80-8	6PR	16.4 / 417	4.5 / 114	50	3.5	610	275	3.75	8
V-6633	4.10 / 3.50-4	2PR	10.6 / 268	3.7 / 94	30	2.1	232	105	3.25	4
V-6633	4.10 / 3.50-4	4PR	10.6 / 268	3.7 / 94	36	2.5	352	160	3.25	4
V-6633	4.10 / 3.50-4	6PR	10.6 / 268	3.7 / 94	50	3.5	473	215	3.25	4
V-6633	4.10 / 3.50-5	4PR	11.6 / 294	3.4 / 87	36	2.5	415	190	3.25	5
V-6635	200 x 50	2PR	7.5 / 190	1.7 / 44	30	2.1	165	75	200 x 50	4
V-6635	200 x 50	4PR	7.5 / 190	1.7 / 44	36	2.5	271	123	200 x 50	4
V-6635	4.10 / 3.50-6	2PR	17.1 / 434	4.2 / 106	30	2.1	330	150	2.50	6
V-6635	4.10 / 3.50-6	4PR	17.1 / 434	4.2 / 106	36	2.5	460	210	2.50	6
V-6635	4.10 / 3.50-6	6PR	17.1 / 434	4.2 / 106	50	3.5	595	270	2.50	6
V-6635	13 x 3.00(3.00-8)	4PR	13 / 330	3.0 / 76	36	2.5	375	170	2.50	8
V-6635	4.80 / 4.00-8	2PR	15.9 / 403	4.1 / 103	30	2.1	365	165	3.75	8
V-6635	4.80 / 4.00-8	4PR	15.9 / 403	4.1 / 103	36	2.5	484	220	3.75	8
V-6637	4.80-8	4PR	16.4 / 417	4.5 / 114	36	2.5	506	230	3.75	8

Light Truck Tire



PATTERN	SIZE	P.R	O.D	S.W	INFLATION		MAXLOAD		R.W.INCHES	
		PLY	In / mm	In / mm	P.S.I	BAR	LBS	KGS	Width	Inches
V-7219	5.00-12	14PR	23.66 / 601	5.91 / 150	90	6.3	1590	1650	720	3.50B
V-7319	5.00-12	8	22.4 / 568	5.6 / 143	58	4.0	1025	1070	465	3.50B
V-7319	5.00-12	10	22.4 / 568	5.6 / 143	71	5.0	1160	1225	555	3.50B
V-7319	5.00-12	12	22.4 / 568	5.6 / 143	90	6.3	1480	1575	670	3.50B
V-7319	5.00-12	14	22.4 / 568	5.6 / 143	90	6.3	1590	1650	720	3.50B
V-7319	5.50-13	8	24.4 / 620	6.3 / 160	60	4.2	1100	1250	500	4J
V-7319	5.50-13	10	24.4 / 620	6.3 / 160	76	5.3	1280	1445	580	4J
V-7319	5.50-13	12	24.4 / 620	6.3 / 160	85	6.0	1610	1785	730	4J
V-7319	5.50-13	14	24.4 / 620	6.3 / 160	89	6.3	1680	1850	760	4J
V-7319	6.00-13	14PR	25.98 / 660	6.77 / 170	90	6.3				4.5J
V-7319	7.00-16	10TT	30.5 / 775	7.9 / 200	76	5.3	2130	2425	985	1100
V-7319	7.00-16	12TT	30.5 / 775	7.9 / 200	90	6.3	2370	2690	1075	1220
V-7319	7.00-16	14TT	30.5 / 775	7.9 / 200	104	7.3	2565	2910	1165	1320

Light Truck Tire



PATTERN	SIZE	P.R	O.D	S.W	INFLATION		MAXLOAD			R.W.INCHES		
		PLY	In / mm	In / mm	P.S.I	BAR	LBS D	LBS S	KGS D	KGS S	Width	Inches
V-7319	7.00-16	16TT	30.5 / 775	7.9 / 200	110	7.7	2755	3110	1250	1410	5.50F	16
V-7319	7.50-16	16TT	31.7 / 805	8.5 / 215	110	7.7	3440	3660	1560	1660	6.00G	16
V-7319	8.25-16	18TT	33.7 / 855	9.3 / 235	110	7.7	3900	4365	1770	1980	6.50H	16
V-7512	5.00-12	8TT	22.4 / 568	5.6 / 143	57	4.0	1025	1070	465	485	3.50B	12
		10TT	22.4 / 568	5.6 / 143	71	5.0	1160	1225	525	555	3.50B	12
		12TT	22.4 / 568	5.6 / 143	90	6.3	1480	1575	670	715	3.50B	12
		14TT	22.4 / 568	5.6 / 143	90	6.3	1590	1650	720	750	3.50B	12
V-7518	5.50-13	8TT	24.4 / 620	6.3 / 160	60	4.2	1100	1245	500	565	4J	13
		10TT	24.4 / 620	6.3 / 160	76	5.3	1280	1445	580	655	4J	13
		12TT	24.4 / 620	6.3 / 160	85	6.0	1610	1785	730	810	4J	13
V-7518	6.00-14	8TT	26.8 / 680	6.7 / 170	60	4.2	1320	1510	600	685	4.1/2J	14
		14TT	26.8 / 680	6.7 / 170	90	6.3	1850	2095	840	950	4.1/2J	14
V-7518	6.50-15	8TT	28.7 / 730	7.1 / 180	60	4.2	1588	1810	720	820	4.50E	15
		10TT	28.7 / 730	7.1 / 180	76	5.3	1875	2095	850	950	4.50E	15
V-7518	7.00-15	10TT	29.5 / 750	7.9 / 200	76	5.3	2020	2295	915	1040	5.50F	15
		10TT	29.5 / 750	7.3 / 186	76	5.3	1895	2150	860	975	5.50F	16
V-7518	6.50-16	12TT	29.5 / 750	7.3 / 186	90	6.3	2160	2415	980	1095	5.50F	16
		14TT	29.5 / 750	7.3 / 186	90	6.3	2335	2620	1060	1190	5.50F	16
V-7518	7.00-16	12TT	30.5 / 775	7.9 / 200	90	6.3	2370	2690	1075	1220	5.50F	16
		8TT	31.7 / 805	8.5 / 215	60	4.2	2140	2435	970	1105	6.00G	16
V-7518	7.50-16	10TT	31.7 / 805	8.5 / 215	76	5.3	2440	2780	1105	1260	6.00G	16
		14TT	31.7 / 805	8.5 / 215	107	7.5	3090	3420	1400	1550	6.00G	16
		16TT	31.7 / 805	8.5 / 215	110	7.7	3310	3660	1500	1660	6.00G	16
V-7518	8.25-16	14TT	33.7 / 855	9.3 / 235	90	6.3	3310	3760	1500	1705	6.50H	16
		16TT	33.7 / 855	9.3 / 235	110	7.7	3620	4080	1640	1850	6.50H	16
V-7519	7.00-16	12TT	30.5 / 775	7.9 / 200	90	6.3	2370	2690	1075	1220	5.50F	16
		14TT	30.5 / 775	7.9 / 200	105	7.3	2565	2910	1165	1320	5.50F	16
V-7519	7.50-16	14TT	31.7 / 805	8.5 / 215	107	7.5	3090	3420	1400	1550	6.00G	16
		16TT	31.7 / 805	8.5 / 215	110	7.7	3310	3660	1500	1660	6.00G	16
V-7529	6.00-14	8TT	26.8 / 680	6.7 / 170	60	4.2	1320	1510	600	685	4.1/2J	14
		10TT	26.8 / 680	6.7 / 170	75	5.3	1520	1720	690	780	4.1/2J	14
		12TT	26.8 / 680	6.7 / 170	90	6.3	1720	1950	780	885	4.1/2J	14
V-7529	8.25-16	14TT	33.7 / 855	9.3 / 235	90	6.3	3310	3760	1500	1705	6.50H	16
		16TT	33.7 / 855	9.3 / 235	110	7.7	3620	4080	1640	1850	6.50H	16
		18TT	33.7 / 855	9.3 / 235	110	7.7	3900	4365	1770	1980	6.50H	16
V-7557	5.50-13	10TT	24.4 / 620	6.3 / 160	77	5.3	1280	1444	580	655	4J	13
		12TT	24.4 / 620	6.3 / 160	85	6.0	1610	1786	730	810	4J	13
		8TT	26.8 / 680	6.7 / 170	60	4.2	1320	1510	600	685	4.1/2J	14
V-7557	6.00-14	12TT	26.8 / 680	6.7 / 170	90	6.3	1720	1950	780	885	4.1/2J	14
		8TT	27.8 / 705	7.1 / 180	60	4.2	1520	1730	690	785	5J	14
V-7557	6.50-14	10TT	27.8 / 705	7.1 / 180	75	5.3	1740	1985	790	900	5J	14
		14TT	27.8 / 705	7.1 / 180	90	6.3	2180	2470	990	1120	5J	14
V-7557	6.50-15	14PR	28.94 / 735	7.17 / 180	105	7.3					4.50E	15
		16PR	28.94 / 735	7.17 / 180	105	7.3					4.50E	15
V-7557	7.00-16	8TT	30.5 / 775	7.9 / 200	60	4.2	1875	2128	850	965	5.50F	16
		10TT	30.5 / 775	7.9 / 200	76	5.3	2130	2425	965	1100	5.50F	16
		12TT	30.5 / 775	7.9 / 200	90	6.3	2370	2690	1075	1220	5.50F	16
		14TT	30.5 / 775	7.9 / 200	104	7.3	2565	2910	1165	1320	5.50F	16
		16TT	30.5 / 775	7.9 / 200	110	7.7	2755	3110	1250	1410	5.50F	16
V-7557	7.50-16	12TT	31.7 / 805	8.5 / 215	90	6.3	2735	3100	1240	1405	6.00G	16
		14TT	31.7 / 805	8.5 / 215	107	7.5	3090	3420	1400	1550	6.00G	16
		16TT	31.7 / 805	8.5 / 215	110	7.7	3310	3660	1500	1660	6.00G	16
V-7557	8.25-16	14TT	33.7 / 855	9.3 / 235	90	6.3	3310	3760	1500	1705	6.50H	16
		16TT	33.7 / 855	9.3 / 235	110	7.7	3620	4080	1640	1850	6.50H	16
		18TT	33.7 / 855	9.3 / 235	110	7.7	3900	4365	1770	1980	6.50H	16
V-7711	5.00-12	8TT	22.40 / 568	5.60 / 143	58	4.0	1025	1070	465	485	3.50B	12
		12TT	22.40 / 568	5.60 / 143	90	6.3	1480	1575	670	715	3.50B	12
V-7711	7.50-16	8TT	31.70 / 805	8.50 / 215	60	4.2	2140	2436	970	1105	6.00G	16
		10TT	31.70 / 805	8.50 / 215	76	5.3	2440	2778	1105	1260	6.00G	16
		12TT	31.70 / 805	8.50 / 215	90	6.3	2735	3100	1240	1405	6.00G	16
		14TT	31.70 / 805	8.50 / 215	107	7.5	3090	3420	1400	1550	6.00G	16
		16TT	31.70 / 805	8.50 / 215	110	7.7	3310	3660	1500	1660	6.00G	16

Trailer Tire

PATTERN	SIZE	P.R	O.D	S.W	INFLATION		MAXLOAD		R.W.INCHES	
		PLY	In / mm	In / mm	P.S.I	BAR	LBS	KGS	Width	Inches
V-7582	4.00-10	6PR	18.5 / 470	4.3 / 109	50	3.5	773	350	3.00	3.00
V-7582	4.50-10	4PR	19.4 / 494	5.0 / 127	50	3.5	715	325	3.50	3.50
V-7582	4.50-10	6PR	19.4 / 494	5.0 / 127	60	4.25	883	400	3.50	3.50
V-7582	4.50-10	8PR	19.4 / 494	5.0 / 127	74	5.2	965	437	3.50	3.50
V-7582	5.00-10	4PR	20.5 / 521	5.7 / 146	50	3.5	782	355	3.50B	3.50
V-7582	5.00-10	6PR	20.5 / 521	5.7 / 146	57	4.0	971	440	3.50B	3.50
V-7582	5.00-10	8PR	20.5 / 521	5.7 / 146	71	5.0	1104	500	3.50B	3.50
V-7711	5.00-10	4PR	20.4 / 517	5.6 / 143	50	3.5	785	355	3.50	10
		8PR	20.4 / 517	5.6 / 143	71	5.0	1105	500	3.50	10
		10PR	20.4 / 517	5.6 / 143	85	6.0	1345	610	3.50	10
		12PR	20.4 / 517	5.6 / 143	90	6.3	1575	715	3.50	10
V-7761	6.00-9	4PR	20.2 / 514	6.9 / 176	50	3.4	1045	475	5.00	9
V-7761	6.00-9	6PR	20.2 / 514	6.9 / 176	75	5.2	1320	600	5.00	9
V-7762	5.00-10	4PR	20.1 / 511	5.4 / 137	50	3.5	782	355	3.50	10
V-7763	5.00-8	4PR	17.9 / 456	5.5 / 140	50	3.4	715	325	3.00	8
V-7763	5.00-8	6PR	17.9 / 456	5.5 / 140	75	5.2	910	415	3.00	8
V-7768	4.50-10	4PR	19.1 / 486	5.0 / 127	50	3.5	720	325	3.00	10
		6PR	19.1 / 486	5.0 / 127	60	4.3	880	400	3.00	10
		8PR	19.1 / 486	5.0 / 127	54	4.5	1020	462	3.00	10
		10PR	19.1 / 486	5.0 / 127	71	5.0	1050	475	3.00	10
V-9128	3.50-8	4PR	15.2 / 386	3.4 / 86	36	2.5	375	170	2.50	8
KT-701	4.80-8	4PR	16.34 / 415	4.72 / 120	57	4.0	585	265	3.75	8
		6PR	16.34 / 415	4.72 / 120	71	5.0	739	335	3.75	8
KT-701	5.70-8	4PR	18.50 / 470	6.30 / 160	50	3.40	715	325	4.50	8
		6PR	18.50 / 470	6.30 / 160	75	5.20	908	412	4.50	8
		8PR	18.50 / 470	6.30 / 160	100	6.90	1070	487	4.50	8
KT-701	4.80-12	4PR	20.75 / 527	4.72 / 120	60	4.20	780	355	3.75	12
		6PR	20.75 / 527	4.72 / 120	90	6.20	990	450	3.75	12
KT-701	5.30-12	4PR	22.05 / 560	5.91 / 150	55	3.80	855	387	4.25	12
		6PR	22.05 / 560	5.91 / 150	80	5.50	1045	475	4.25	12
KT-705	16.5 x 6.5-8	4PR	16.73 / 425	6.38 / 162	45	3.10	620	280	5.375	8
		6PR	16.73 / 425	6.38 / 162	70	4.80	805	365	5.375	8
		8PR	16.73 / 425	6.38 / 162	90	6.20	908	412	5.375	8
KT-705	18.5 x 8.5-8	4PR	18.90 / 480	8.19 / 208	35	2.40	760	345	7.00	8
		6PR	18.90 / 480	8.19 / 208	50	3.40	935	425	7.00	8
KT-705	20.5 x 8.0-10	4PR	21.06 / 535	8.23 / 209	35	2.40	905	410	6.00	10
		6PR	21.06 / 535	8.23 / 209	50	3.40	1105	500	6.00	10
		8PR	21.06 / 535	8.23 / 209	70	4.80	1320	600	6.00	10
KT-715	4.00-10	4PR	18.50 / 470	4.45 / 113	43	3.00	600	272	2.50	10
		6PR	18.50 / 470	4.45 / 113	50	3.50	761	345	3.00	10
KT-715	4.50-10	4PR	19.13 / 486	5.00 / 127	50	3.50	717	325	3.00B	10
		6PR	19.13 / 486	5.00 / 127	60	4.30	882	400	3.00B	10
KT-715	5.00-10	4PR	20.63 / 524	5.63 / 143	50	3.50	782	355	3.50B	10
		6PR	20.63 / 524	5.63 / 143	57	4.00	963	437	3.50B	10
		8PR	20.63 / 524	5.63 / 143	71	5.00	1103	500	3.50B	10
KT-729	ST175 / 80D13	6PR	24.02 / 610	6.85 / 174	50	3.50	1360	615	5.00	13
KT-747	145-10	4PR	19.09 / 485	5.71 / 145	40	2.80	695	315	4.00	10
		6PR	19.09 / 485	5.71 / 145	50	3.40	882	400	4.00	10
KT-7166	195 / 50B10		17.80 / 452	7.56 / 192	85	6.00	1655	750	6.00	10

Go Kart Tire

PATTERN	SIZE	TT/TL	COMPOUND	O.D	S.W	R.W.
				In / mm	In / mm	Inch
KT-735	10.5 * 4.50-6	TL		11.65 / 296	5.63 / 143	6.50
KT-735	11 * 6.00-6	TL		12.01 / 305	7.20 / 183	8.50
KT-736	12 * 4.00-5	TT	SL68 / SL72	11.85 / 301	4.09 / 104	3.25
KT-738	4.10 / 3.50-4	TT/TL	SL68 / SL72	10.31 / 262	4.09 / 104	2.75
KT-739	9 * 3.50-4	TT/TL	SL68 / SL72	8.66 / 220	3.62 / 92	2.75
KT-739	10 * 4.50-5	TL	SL62 / SL68 / SL72	10.24 / 260	5.39 / 137	5.00
KT-739	11 * 6.00-5	TL	SL68 / SL72	11.57 / 294	7.64 / 194	7.00
KT-739	11 * 7.10-5	TL	SL62 / SL68 / SL72	11.57 / 294	8.27 / 210	7.50
KT-739	4.10 / 3.50-5	TT/TL	SL68 / SL72	11.30 / 287	4.09 / 104	3.25
KT-739	13 * 5.00-6	TL	SL68 / SL72	12.68 / 322	4.72 / 120	3.50

Agricultural Tractor Tire

PATTERN	SIZE	P.R	O.D	S.W	INFLATION		MAXLOAD		R.W.INCHES	
		PLY	In / mm	In / mm	P.S.I	BAR	LBS	KGS	Width	Inches
V-8501	13 * 5.00-6	2PR	12.68 / 322	4.57 / 116	22	1.50	295	135	3.50	6
V-8501	4.80 / 4.00-8	2PR	16.7 / 424	4.4 / 112	22	1.5	342	155	3.00	8
V-8501	4.80 / 4.00-8	4PR	16.7 / 424	4.4 / 112	40	2.8	496	225	3.00	8
V-8501	16 x 6.50-8	2PR	16.34 / 415	6.50 / 165	14	1.0	385	175	5.375	8
		4PR	16.34 / 415	6.50 / 165	28	2.0	584	265	5.375	8
		6PR	16.34 / 415	6.50 / 165	36	2.5	685	310	5.375	8
V-8501	5.00-10	4PR	20.6 / 522	5.4 / 136	33	2.3	551	250	3.00	10
V-8501	6.5 / 80-15	4TT	26.8 / 680	6.4 / 163	34	2.4	940	425	5.00	15
		6TT	26.8 / 680	6.4 / 163	52	3.6	1210	550	5.00	15
V-8502	3.00-4	2PR	10.4 / 264	3.4 / 86	25	1.75	156	71	2.15	4
V-8502	4.00-4	4PR	12.3 / 313	4.5 / 114	40	2.8	342	155	3.00	4
V-8502	3.50-6	4PR	13.5 / 343	3.9 / 100	43	3.0	364	165	2.50	6
V-8502	4.00-6	4PR	14.25 / 362	4.53 / 115	36	2.50	265	120	3.00	6
		6PR	14.25 / 362	4.53 / 115	40	3.80	300	135	3.00	6

Agricultural Tractor Tire

PATTERN	SIZE	P.R	O.D	S.W	INFLATION		MAXLOAD		R.W.INCHES	
		PLY	In / mm	In / mm	P.S.I	BAR	LBS	KGS	Width	Inches
V-8502	3.50-8	4PR	15.6 / 395	3.9 / 100	43	3.0	408	185	2.50	8
V-8502	4.00-8	4PR	16.8 / 426	4.3 / 108	43	3.0	496	225	2.50	8
V-8502	4.80-8	4PR	16.8 / 426	4.3 / 108	43	3.0	496	225	2.50	8
V-8502	5.50-16	6PR	28.3 / 718	6.0 / 152	55	3.7	1168	530	4.00	16
V-8502	6.00-16	6PR	29.1 / 738	6.7 / 169	48	3.3	1235	560	4.00	16
V-8504	3.50-6	2PR	13.6 / 346	3.9 / 100	21	1.5	247	112	2.50	6
V-8504	3.50-6	4PR	13.6 / 346	3.9 / 100	43	3	365	165	2.50	6
V-8506	19 x 8.00-10	4TT	18.5 / 470	7.7 / 195	21	1.5	815	370	6.50	10
		6TT	18.5 / 470	7.7 / 195	33	2.3	990	450	6.50	10
V-8508	10-16.5	8TL	30.4 / 773	10.4 / 264	60	4.1	4140	1880	8.25	16.5
V-8509	5.00-12	4TT	22.2 / 563	5.3 / 134	28	1.9	615	280	4.00	12
		6TT	22.2 / 563	5.3 / 134	36	2.5	770	350	4.00	12
V-8509	5.50-13	4TT	24.6 / 625	5.9 / 150	28	1.9	760	345	4.00	13
		6TT	24.6 / 625	5.9 / 150	40	2.8	860	390	4.00	13
		8TT	24.6 / 625	5.9 / 150	58	4.0	1050	475	4.00	13
V-8509	6.00-14	8TT	27.2 / 690	6.5 / 165	43	3.0	1100	500	4.50E	14
V-8588	16 x 6.50-8	4PR	15.94 / 405	6.5 / 165	28	1.9	585	265	5.375	8
V-8803	3.00-4	2PR	10.8 / 275	3.5 / 88	25	1.75	110	50	2.15	4
V-8803	4.00-4	4PR	12.3 / 313	4.5 / 114	40	2.8	240	109	3.00	4
V-8803	3.50-6	4PR	13.7 / 347	4.1 / 105	43	3.0	253	115	2.50	6
V-8803	13 x 5.00-6	4PR	12.8 / 326	4.8 / 122	24	1.7	374	170	3.00	6
V-8803	3.50-8	4PR	15.5 / 393	4.1 / 105	40	2.8	297	135	2.50	8
V-8803	4.00-8	4PR	16.0 / 407	4.2 / 106	40	2.8	352	160	2.50	8
V-8803	4.00-8	6PR	16.0 / 407	4.2 / 106	58	4.0	454	206	2.50	8
V-8803	4.00-10	4TT	19.4 / 494	4.5 / 115	40	2.8	410	185	3.00	10
V-8803	4.50-10	4TT	20.0 / 508	4.6 / 118	40	2.8	467	212	3.00	10
V-8803	5.00-10	4TT	20.6 / 518	5.4 / 138	2.3	550	250	250	3.50	10
		6TT	20.6 / 518	5.4 / 138	2.8	705	320	320	3.50	10
V-8803	5.00-12	4PR	23.0 / 586	5.6 / 142	32	2.2	616	280	4.00E	12
V-8803	6.00-12	4PR	24.3 / 618	6.1 / 154	26	1.8	738	335	4.00E	12
V-8813	4.00-4	4PR	12.3 / 313	4.7 / 116	40	2.8	240	109	3.00	4
V-8813	5.00-8	4PR	16.7 / 424	5.4 / 136	21	1.4	542	246	275	8
V-8813	5.00-10	4PR	20.4 / 518	5.4 / 137	33	2.3	551	250	3.50	10
V-8814	3.50-5	4TT	12.2 / 310	3.5 / 88	36	2.5	350	160	2.50	5
V-8816	4.00-8	4PR	17.2 / 436	4.3 / 109	40	2.8	352	160	2.75	8
V-8816	4.00-10	4PR	18.7 / 474	4.3 / 110	40	2.8	407	185	3.00	10
V-8817	16 x 6.50-8	4PR	16.5 / 418	6.1 / 156	25	1.9	617	280	5.375	8
V-8818	4.00-7	2TT	14.9 / 380	4.5 / 114	21	1.5	225	100	3.00	7
		4TT	14.9 / 380	4.5 / 114	36	2.5	330	150	3.00	7
V-8819	3.50-7	4TT	14.3 / 362	3.5 / 90	40	2.8	309	140	2.50	7
V-8911	10-16.5	8TL	30.4 / 773	10.4 / 264	60	4.1	4140	1880	8.25	16.5
V-8911	12-16.5	10TL	32.7 / 831	12.1 / 307	65	4.5	5600	2540	9.75	16.5