



GOODTIME

TIRES AND TUBES MANUFACTURER



GOODTIME RUBBER CO., LTD.

Factory: KM32, National Road 22, An Tinh Village,
Trang Bang District, Tay Ninh Province, Vietnam

Tel: 886-4-8322568 Fax: 886-4-8331186

[Http://www.goodtimegroup.com.tw](http://www.goodtimegroup.com.tw)

E-mail: sales@mail.goodtimegroup.com.tw



DOT
ISO 9001



INDEX



▪ STANDARD STREET
MOTORCYCLE TIRE
P01~P03



▪ HI-SPEED TIRE
▪ ALL KINDS OF TUBES
P12



▪ SCOOTER TIRE
P04~P10

SIZE	PR	PLY	It
3.00-18	6PR		24.4
3.50-18	4PR		25.7
2.75-16	4PR		22.0
2.25-17	4PR		22.1
2.50-17	4PR		22
2.50-17	6PR		27
2.75-17	4PR		
2.75-17	6PR		
50-17	4PR		

▪ TECHNICAL DATA
P13~P17



▪ OFF ROAD TIRE
P11

STANDARD STREET MOTORCYCLE TIRE



V-9131
2.50-17



V-9132
2.75-14
2.50-16
2.50-17
2.75-17
2.75-18



V-9133
3.00-16
3.00-17



V-9331
2.50-17



V-9332
2.75-17



V-9333
2.75-17



V-9335
2.50 - 17



V-9336
2.25 - 17



V-9338
2.50 - 17



V-9339
2.50 - 17



V-9513
2.75 - 17



V-9516
2.25 - 18

STANDARD STREET MOTORCYCLE TIRE

STANDARD STREET MOTORCYCLE TIRE



V-9536

2.25-17
2.50-17
80 / 90-17
2.50-18
80 / 90-18



V-9550

2.25-17



V-9568

2.50-17
70 / 90-17
80 / 90-17



V-9589

70 / 90-14
80 / 90-14
90 / 90-14
70 / 90-16
80 / 90-16



V-9922

2.50-17



V-9924

2.25-17
2.50-17
2.75-17
3.00-17
2.50-18



V-9925

2.75-17
2.50-18



V-9926

2.75-14
2.25-17
2.75-18



V-9927

3.00-18



V-9598

70 / 100-17
80 / 90-17



V-9887

80 / 90-14
90 / 90-14
70 / 90-16
80 / 90-16



V-9917

3.00-17
3.25-17



V-9918

2.25-16 2.50-18
2.75-17 2.75-18
3.00-17 3.00-18
3.25-17 3.50-18



V-9919

2.75-16
2.25-17
2.50-17
2.75-17



V-9928

2.25-17



V-9932

2.75-17



V-9937

2.75-17



V-9950

2.25-17

SCOOTER TIRE



V-9001

140 / 70-12



V-9002

110 / 70-12



V-9003

120 / 70-14
140 / 60-14



V-9005

120 / 80-10



V-9006

130 / 70-10



V-9009

110 / 70-12
120 / 70-12



V-9011

3.50-10
110 / 90-10



V-9012

3.50-10



V-9013

90 / 90-10



V-9019

3.50-10

SCOOTER TIRE



V-9035

3.00-10
3.50-10
100 / 90-10



V-9039

90 / 90-10



V-9049

90 / 90-10



V-9071

90 / 90-10



V-9126

3.50-10



V-9128

3.50-8
4.00-8
2.75-10
3.00-10
3.50-10



V-9282

3.00-10
3.50-10
90 / 90-10
100 / 90-10



V-9283

3.00-10
3.50-10
90 / 90-10
100 / 90-10



V-9286

3.00-10
3.50-10
90 / 90-10
100 / 90-10



V-9288

3.00-10
3.50-10
90 / 90-10
100 / 90-10

SCOOTER TIRE



V-9293

120 / 70-12
130 / 70-12



V-9295

3.00-10
3.50-10
90 / 90-10
100 / 90-10



V-9297

3.00-10
3.50-10
90 / 90-10
100 / 90-10



V-9298

3.00-10
3.50-10
90 / 90-10
100 / 90-10



V-9299

100 / 90-10



V-9501

120 / 70-12



V-9505

3.50-10



V-9525

90 / 90-10



V-9529

2.75-10



V-9538

3.50-10

SCOOTER TIRE



V-9542

3.00-10
3.50-10
90 / 90-10
100 / 90-10
120 / 90-10
130 / 90-10
130 / 70-13



V-9546

110 / 90-13



V-9548

100 / 90-10



V-9552

3.50-10



V-9553

3.50-10



V-9556

3.00-10
3.50-10



V-9558

3.00-10



V-9576

3.50-10



V-9578

4.00-10



V-9596

140 / 70-12

SCOOTER TIRE



V-9597

130 / 60-13
140 / 60-13



V-9611

3.00-10



V-9612

3.50-10



V-9617

3.00-10
90 / 90-10
100 / 90-10



V-9618

3.00-10
3.50-10
90 / 90-10
100 / 90-10



V-9622

90 / 90-10



V-9625

100 / 90-10



V-9639

3.50-10



V-9666

3.50-10



V-9888

90 / 90-10
100 / 90-10

SCOOTER TIRE



V-9906

130 / 70-12



V-9910

90 / 90-10
100 / 90-10



V-9912

3.50-10



V-9913

3.50-10



V-9920

3.00-10
3.50-10
90 / 90-10
100 / 90-10
110 / 80-12
120 / 70-12
130 / 70-12



V-9937

3.00-10
3.50-10
90 / 90-10
100 / 80-10
100 / 90-10



V-9945

3.00-10
3.50-10
90 / 90-10
100 / 90-10



V-9956

3.00-10
3.50-10



V-9957

100 / 90-10



V-9967

120 / 90-10
130 / 90-10

SCOOTER TIRE



V-9968

3.00-10



V-9972

100 / 90-10



V-9973

3.00-10
3.50-10
90 / 90-10
100 / 80-10
100 / 90-10



V-9985

3.50-10
100 / 90-10



V-9986

3.00-10



V-9989

3.50-10
90 / 90-10
100 / 90-10
110 / 90-10



V-9990

3.50-10



V-9995

120 / 70-10



V-9999

90 / 90-10
100 / 90-10



KT-903

4.00-8

OFF ROAD TIRE



V-9962

2.75-17



V-9963

2.75-19



V-9965

100 / 100-18



V-9966

2.75-17
3.00-17



V-9998

120 / 90-10
130 / 90-10



HI-SPEED TIRE



V-9588

60 / 80-17
70 / 80-17
70 / 90-17
80 / 80-17
80 / 90-17
90 / 80-17

V-9871

110 / 70-17

V-9872

140 / 70-17

KT-909

90 / 90-18

ALL KINDS OF TUBES



KT-975

90 / 80-17
100 / 80-17
110 / 80-17
120 / 80-17



Standard Street Motorcycle Tire

PATTERN	SIZE	P.R.	O.D.	S.W.	INFLATION		MAXLOAD		R.W.INCHES	
		PLY	In / mm	In / mm	P.S.I	BAR	LBS	KGS	Width	Inches
V-9131	2.50-17	4PR	22.6 / 574	2.6 / 65	32	2.3	290	132	1.50	17
V-9131	2.50-17	6PR	22.6 / 574	2.6 / 65	40	2.8	385	172	1.50	17
V-9132	2.75-14	4PR	20.2 / 512	2.8 / 70	32	2.3	267	121	1.85	14
V-9132	2.75-14	6PR	20.2 / 512	2.8 / 70	40	2.8	267	121	1.85	14
V-9132	2.50-16	4PR	21.0 / 534	2.4 / 60	32	2.3	277	126	1.60	16
V-9132	2.50-17	4PR	22.6 / 573	2.6 / 65	32	2.3	290	132	1.50	17
V-9132	2.50-17	6PR	22.6 / 573	2.6 / 65	40	2.8	335	152	1.50	17
V-9132	2.75-17	4PR	23.0 / 585	2.8 / 70	32	2.3	335	152	1.85	17
V-9132	2.75-17	6PR	23.0 / 585	2.8 / 70	40	2.8	380	172	1.85	17
V-9132	2.50-18	4PR	23.1 / 586	2.4 / 62	32	2.3	310	140	1.60	18
V-9132	2.50-18	6PR	23.1 / 586	2.4 / 62	40	2.8	335	152	1.60	18
V-9132	2.75-18	4PR	23.9 / 606	2.8 / 70	32	2.3	335	152	1.85	18
V-9132	2.75-18	6PR	23.9 / 606	2.8 / 70	40	2.8	400	180	1.85	18
V-9133	3.00-16	4PR	22.4 / 568	2.9 / 74	32	2.3	361	164	1.85	16
V-9133	3.00-17	4PR	23.5 / 598	3.0 / 77	32	2.3	380	172	1.85	17
V-9331	2.50-17	4PR	22.6 / 574	2.0 / 64	32	2.3	290	132	1.50	17
V-9331	2.50-17	6PR	22.6 / 574	2.5 / 64	40	2.8	335	152	1.50	17
V-9332	2.75-17	4PR	23.1 / 586	2.9 / 73	32	2.3	335	152	1.85	17
V-9332	2.75-17	6PR	23.1 / 586	2.9 / 73	40	2.8	380	172	1.85	17
V-9333	2.75-17	4PR	23.1 / 587	2.9 / 73	32	2.3	335	152	1.85	17
V-9333	2.75-17	6PR	23.1 / 587	2.9 / 73	40	2.8	380	172	1.85	17
V-9335	2.50-17	4PR	22.6 / 574	2.6 / 65	32	2.3	290	132	1.50	17
V-9336	2.25-17	4PR	21.8 / 554	2.3 / 58	32	2.3	256	116	1.40	17
V-9338	2.50-17	4PR	22.4 / 568	2.5 / 64	33	2.3	291	132	1.60	17
V-9338	2.50-17	6PR	22.4 / 568	2.5 / 64	40	2.8	341	155	1.60	17
V-9339	2.50-17	4PR	22.4 / 568	2.5 / 64	32	2.3	290	132	1.60	17
V-9513	2.75-17	4PR	23.1 / 588	2.8 / 72	36	2.5	320	145	1.85	17
V-9516	2.25-18	4PR	23.1 / 586	2.3 / 58	33	2.3	208	94	1.40	18
V-9536	2.25-17	4PR	21.9 / 556	2.4 / 61	33	2.3	256	116	1.60	17
V-9536	2.50-17	4PR	22.4 / 568	2.5 / 64	32	2.3	290	132	1.60	17
V-9536	80 / 90-17	4PR	22.8 / 578	3.1 / 78	33	2.3	353	160	1.85	17
V-9536	2.50-18	4PR	23.3 / 593	2.5 / 64	33	2.3	309	140	1.50	18
V-9550	2.25-17	4PR	21.9 / 556	2.4 / 61	32	2.3	254	116	1.60	17
V-9568	2.50-17	4PR	22.36 / 568	2.56 / 65	32	2.3	290	132	1.60	17
V-9568	2.50-17	6PR	22.36 / 568	2.56 / 65	40	2.8	342	155	1.60	17
V-9568	70 / 90-17	4PR	21.65 / 550	2.48 / 63	33	2.3	290	132	1.60	17
V-9568	70 / 90-17	6PR	21.65 / 550	2.48 / 63	40	2.8	341	155	1.60	17
V-9568	80 / 90-17	4PR	22.68 / 576	3.15 / 80	33	2.3	353	160	1.85	17
V-9568	80 / 90-17	6PR	22.68 / 576	3.15 / 80	40	2.8	419	190	1.85	17
V-9589	70 / 90-14	4PR	18.9 / 480	2.7 / 69	33	2.3	253	115	1.60	14
V-9589	80 / 90-14	6PR	19.7 / 500	3.15 / 80	40	2.8	396	180	1.85	14
V-9589	90 / 90-14	4PR	20.5 / 520	3.1 / 80	33	2.3	353	160	2.15	14
V-9589	70 / 90-16	4PR	20.9 / 532	2.7 / 69	40	2.8	330	150	1.60	16
V-9589	80 / 90-16	4PR	21.7 / 550	3.1 / 80	40	2.8	397	180	1.85	16
V-9598	70 / 100-17	4PR	22.52 / 572	2.72 / 69	33	2.3	310	140	1.60	17
V-9598	80 / 90-17	4PR	22.76 / 578	3.07 / 78	33	2.3	353	160	1.85	17
V-9598	80 / 90-17	6PR	22.76 / 578	3.07 / 78	40	2.8	419	190	1.85	17
V-9887	80 / 90-14	4PR	19.69 / 500	2.99 / 76	33	2.3	310	140	1.85	14
V-9887	80 / 90-14	6PR	19.69 / 500	2.99 / 76	40	2.8	375	170	1.85	14
V-9887	90 / 90-14	4PR	20.47 / 520	3.27 / 83	33	2.3	375	170	2.15	14
V-9887	90 / 90-14	6PR	20.47 / 520	3.27 / 83	40	2.8	441	200	2.15	14
V-9887	70 / 90-16	4PR	20.94 / 532	2.72 / 69	33	2.3	276	125	1.60	16
V-9887	70 / 90-16	6PR	20.94 / 532	2.72 / 69	40	2.8	330	150	1.60	16
V-9887	80 / 90-16	4PR	21.65 / 550	2.91 / 74	33	2.3	342	155	1.85	16
V-9887	80 / 90-16	6PR	21.65 / 550	2.91 / 74	40	2.8	396	180	1.85	16
V-9917	3.00-17	4PR	23.70 / 602	3.15 / 80	33	2.3	365	165	1.85	17
V-9917	3.00-17	6PR	23.70 / 602	3.15 / 80	40	2.8	419	190	1.85	17
V-9917	3.00-17	4PR	24.17 / 614	3.50 / 89	33	2.3	419	190	2.15	17
V-9917	3.25-17	6PR	24.17 / 614	3.50 / 89	40	2.8	507	230	2.15	17
V-9918	2.25-16	4PR	20.9 / 532	2.4 / 60	32	2.3	242	109	1.40	16
V-9918	2.75-17	4PR	23.0 / 584	2.8 / 72	36	2.5	334	151	1.85	17
V-9918	3.00-17	4PR	23.7 / 602	3.0 / 76	36	2.5	334	151	1.85	17
V-9918	3.25-17	4PR	23.9 / 608	3.2 / 82	36	2.5	380	172	1.85	17
V-9918	2.50-18	4PR	23.4 / 594	2.4 / 60	32	2.3	310	140	1.60	18
V-9918	2.75-18	4PR	23.9 / 608	2.8 / 70	32	2.3	335	152	1.85	18
V-9918	2.75-18	6PR	23.9 / 608	2.8 / 70	40	2.8	400	180	1.85	18
V-9918	3.00-18	4PR	24.4 / 621	3.0 / 77	32	2.3	380	172	1.85	18
V-9918	3.00-18	6PR	24.4 / 621	3.0 / 77	40	2.8	441	200	1.85	18
V-9918	3.50-18	4PR	25.7 / 652	3.5 / 90	40	2.8	493	224	2.15	18
V-9919	2.75-16	4PR	22.0 / 560	2.81 / 70	32	2.3	317	144	1.85	17
V-9919	2.25-17	4PR	22.1 / 562	2.2 / 56	40	2.8	291	132	1.40	17
V-9919	2.50-17	4PR	22.1 / 562	2.4 / 60	32	2.3	290	132	1.60	17

Standard Street Motorcycle Tire

PATTERN	SIZE	P.R	O.D	S.W	INFLATION		MAXLOAD		R.W.INCHES	
		PLY	In / mm	In / mm	P.S.I	BAR	LBS	KGS	Width	Inches
V-9919	2.50-17	6PR	22.1 / 562	2.4 / 60	40	2.8	335	152	1.60	17
V-9919	2.75-17	4PR	22.9 / 582	2.8 / 71	32	2.3	335	152	1.85	17
V-9919	2.75-17	6PR	22.9 / 582	2.8 / 71	40	2.8	380	172	1.85	17
V-9922	2.50-17	4PR	22.5 / 571	2.6 / 65	32	2.3	290	132	1.60	17
V-9924	2.25-17	4PR	21.6 / 548	2.3 / 58	32	2.3	256	116	1.40	17
V-9924	2.50-17	4PR	22.4 / 570	2.6 / 66	32	2.3	290	132	1.60	17
V-9924	2.75-17	4PR	22.9 / 581	2.8 / 70	32	2.3	335	152	1.85	17
V-9924	3.00-17	4PR	23.7 / 602	3.1 / 80	33	2.3	364	165	1.85	17
V-9924	2.50-18	4PR	23.4 / 594	2.6 / 65	32	2.3	310	140	1.60	18
V-9925	2.75-17	4PR	23.2 / 589	3.0 / 75	32	2.3	335	152	1.85	17
V-9925	2.75-17	6PR	23.2 / 589	3.0 / 75	40	2.8	380	172	1.85	17
V-9925	2.50-18	4PR	23.3 / 593	2.5 / 64	33	2.3	309	140	1.50	18
V-9926	2.75-14	4PR	20.2 / 512	2.8 / 70	32	2.3	267	121	1.85	14
V-9926	2.25-17	4PR	21.6 / 548	2.3 / 57	32	2.3	256	116	1.40	17
V-9926	2.75-18	4PR	23.9 / 608	2.8 / 70	32	2.3	370	168	1.85	18
V-9927	3.00-18	4PR	24.4 / 620	2.9 / 74	40	2.8	441	200	1.85	18
V-9927	3.00-18	6PR	24.4 / 620	2.9 / 74	40	2.8	441	200	1.85	18
V-9928	2.25-17	4PR	21.9 / 556	2.4 / 61	33	2.3	256	116	1.60	17
V-9932	2.75-17	4PR	22.9 / 581	2.8 / 70	32	2.3	335	152	1.85	17
V-9937	2.75-17	4PR	22.9 / 581	2.8 / 70	32	2.3	335	152	1.85	17
V-9937	2.75-17	6PR	22.9 / 581	2.8 / 70	40	2.8	380	172	1.85	17
V-9950	2.25-17	4PR	21.50 / 546	2.32 / 59	33	2.3	254	115	1.60	17

Scooter Tire

PATTERN	SIZE	P.R	O.D	S.W	INFLATION		MAXLOAD		R.W.INCHES	
		PLY	In / mm	In / mm	P.S.I	BAR	LBS	KGS	Width	Inches
V-9001	140 / 70-12	4PR	19.7 / 501	5.6 / 141	36	2.5	550	250	4.00	12
V-9001	140 / 70-12	6PR	19.7 / 501	5.6 / 141	40	2.8	638	290	4.00	12
V-9002	110 / 70-12	4PR	18.1 / 459	4.3 / 110	33	2.3	385	175	3.00	12
V-9002	110 / 70-12	6PR	18.1 / 459	4.3 / 110	40	2.8	453	206	3.00	12
V-9003	120 / 70-14	4PR	20.6 / 524	4.8 / 122	33	2.3	488	218	3.50	14
V-9003	140 / 60-14	4PR	20.6 / 524	5.5 / 139	33	2.3	520	236	3.75	14
V-9005	120 / 80-10	4PR	17.6 / 446	4.7 / 119	36	2.5	583	265	2.75	10
V-9005	120 / 80-10	6PR	17.6 / 446	4.7 / 119	40	2.8	675	307	2.75	10
V-9006	130 / 70-10	4PR	17.2 / 436	5.1 / 129	33	2.3	440	200	3.50	10
V-9006	130 / 70-10	6PR	17.2 / 436	5.1 / 129	40	2.8	535	243	3.50	10
V-9009	110 / 70-12	4PR	18.1 / 460	4.3 / 110	33	2.3	385	175	3.00	12
V-9009	120 / 70-12	4PR	18.6 / 473	4.8 / 122	33	2.3	430	195	3.50	12
V-9011	3.50-10	4PR	17.0 / 431	3.6 / 92	36	2.5	430	195	2.50	10
V-9011	3.50-10	6PR	17.0 / 431	3.6 / 92	43	3.0	535	243	2.50	10
V-9011	110 / 90-10	8PR	17.9 / 457	4.2 / 107	43	3.0	606	275	4.00	10
V-9012	3.50-10	4PR	17.0 / 433	3.8 / 96	36	2.5	430	195	2.50	10
V-9012	3.50-10	6PR	17.0 / 433	3.8 / 96	43	3.0	535	243	2.50	10
V-9013	90 / 90-10	4PR	16.3 / 413	3.1 / 80	36	2.5	331	150	2.10	10
V-9019	3.50-10	4PR	17.2 / 437	3.6 / 92	36	2.5	429	195	2.50	10
V-9019	3.50-10	6PR	17.2 / 437	3.6 / 92	43	3.0	535	243	2.50	10
V-9035	3.00-10	4PR	16.2 / 413	3.1 / 80	36	2.5	330	150	2.15	10
V-9035	3.00-10	6PR	16.2 / 413	3.1 / 80	43	3.0	418	190	2.15	10
V-9035	3.50-10	4PR	17.1 / 435	3.8 / 97	36	2.5	430	195	2.50	10
V-9035	3.50-10	6PR	17.1 / 435	3.8 / 97	43	3.0	535	243	2.50	10
V-9035	100 / 90-10	4PR	17.3 / 440	4.0 / 101	36	2.5	494	224	2.50	10
V-9039	90 / 90-10	4PR	16.3 / 413	3.1 / 80	36	2.5	331	150	2.10	10
V-9049	90 / 90-10	4PR	16.3 / 413	3.1 / 80	36	2.5	331	150	2.10	10
V-9071	90 / 90-10	4PR	16.3 / 413	3.1 / 80	36	2.5	331	150	2.10	10
V-9126	3.50-10	4PR	17.1 / 435	3.5 / 90	36	2.5	430	195	2.50	10
V-9128	3.50-8	4PR	15.2 / 386	3.4 / 86	36	2.5	375	170	2.50	8
V-9128	4.00-8	4PR	15.7 / 400	4.1 / 104	36	2.5	474	218	3.75	8
V-9128	2.75-10	4PR	15.8 / 402	2.9 / 74	36	2.5	282	128	1.75	10
V-9128	3.00-10	4PR	16.0 / 407	2.9 / 74	36	2.5	330	150	2.10	10
V-9128	3.50-10	4PR	17.1 / 435	3.5 / 90	36	2.5	430	195	2.50	10
V-9282	3.00-10	4PR	16.3 / 413	3.1 / 80	36	2.5	330	150	2.15	10
V-9282	3.00-10	6PR	16.3 / 413	3.1 / 80	43	3.0	418	190	2.15	10
V-9282	3.50-10	4PR	17.2 / 437	3.6 / 92	36	2.5	429	195	2.50	10
V-9282	3.50-10	6PR	17.2 / 437	3.6 / 92	43	3.0	535	243	2.50	10
V-9282	90 / 90-10	4PR	16.4 / 416	3.5 / 90	36	2.5	418	190	2.15	10
V-9282	90 / 90-10	6PR	16.4 / 416	3.5 / 90	43	3.0	493	224	2.15	10
V-9282	100 / 90-10	4PR	17.1 / 434	4.0 / 101	36	2.5	493	224	2.50	10

Scooter Tire

PATTERN	SIZE	P.R	O.D	S.W	INFLATION		MAXLOAD		R.W.INCHES	
		PLY	In / mm	In / mm	P.S.I	BAR	LBS	KGS	Width	Inches
V-9282	100 / 90-10	6PR	17.1 / 434	4.0 / 101	43	3.0	565	257	2.50	10
V-9283	3.00-10	4PR	16.3 / 413	3.1/80	36	2.5	331	150	2.10	10
V-9283	3.50-10	4PR	17.2 / 437	3.6 / 92	36	2.5	430	195	2.50	10
V-9283	90 / 90-10	4PR	16.4 / 416	3.5 / 90	36	2.5	418	190	2.15	10
V-9283	100 / 90-10	4PR	17.3 / 440	4.0 / 101	36	2.5	494	224	2.50	10
V-9286	3.00-10	4PR	16.26 / 413	3.15 / 80	36	2.5	331	150	2.10	10
V-9286	3.50-10	4PR	17.32 / 440	3.98 / 101	36	2.5	430	195	2.50	10
V-9286	90 / 90-10	4PR	16.38 / 416	3.54 / 90	36	2.5	419	190	2.15	10
V-9286	100 / 90-10	4PR	17.32 / 440	3.98 / 101	36	2.5	494	224	2.50	10
V-9288	3.00-10	4PR	16.3 / 413	3.1 / 80	36	2.5	331	150	2.10	10
V-9288	3.50-10	4PR	17.2 / 437	3.6 / 92	36	2.5	430	195	2.50	10
V-9288	90 / 90-10	4PR	16.4 / 416	3.5 / 90	36	2.5	418	190	2.15	10
V-9288	100 / 90-10	4PR	17.3 / 440	4.0 / 101	36	2.5	494	224	2.50	10
V-9293	120/70-12	4PR	18.6 / 473	4.8 / 122	33	2.3	429	195	3.50	12
V-9293	120/70-12	6PR	18.6 / 473	4.8 / 122	40	2.8	519	236	3.50	12
V-9293	130/70-12	4PR	19.2 / 487	5.1 / 129	33	2.3	493	224	3.50	12
V-9293	130/70-12	6PR	19.2 / 487	5.1 / 129	40	2.8	583	265	3.50	12
V-9295	3.00-10	4PR	16.3 / 413	3.1 / 80	36	2.5	330	150	2.15	10
V-9295	3.00-10	6PR	16.3 / 413	3.1 / 80	43	3.0	418	190	2.15	10
V-9295	3.50-10	4PR	17.2 / 437	3.6 / 92	36	2.5	429	195	2.50	10
V-9295	3.50-10	6PR	17.2 / 437	3.6 / 92	43	3.0	535	243	2.50	10
V-9295	90/90-10	4PR	16.4 / 416	3.5 / 90	36	2.5	418	190	2.15	10
V-9295	90/90-10	6PR	16.4 / 416	3.5 / 90	43	3.0	493	224	2.15	10
V-9295	100/90-10	4PR	17.1 / 434	4.0 / 101	36	2.5	493	224	2.50	12
V-9295	100/90-10	6PR	17.1 / 434	4.0 / 101	43	3.0	565	257	2.50	12
V-9297	3.00-10	4PR	16.3 / 413	3.1 / 80	36	2.5	330	150	2.15	10
V-9297	3.00-10	6PR	16.3 / 413	3.1 / 80	43	3.0	418	190	2.15	10
V-9297	3.50-10	4PR	17.2 / 437	3.6 / 92	36	2.5	429	195	2.50	10
V-9297	3.50-10	6PR	17.2 / 437	3.6 / 92	43	3.0	535	243	2.50	10
V-9297	90/90-10	4PR	16.4 / 416	3.5 / 90	36	2.5	418	190	2.15	10
V-9297	90/90-10	6PR	16.4 / 416	3.5 / 90	43	3.0	493	224	2.15	10
V-9297	100/90-10	4PR	17.1 / 434	4.0 / 101	36	2.5	493	224	2.50	10
V-9297	100/90-10	6PR	17.1 / 434	4.0 / 101	43	3.0	565	257	2.50	10
V-9298	3.00-10	4PR	16.26 / 413	3.19 / 81	36	2.5	331	150	2.10	10
V-9298	3.50-10	4PR	17.20 / 437	3.62 / 92	36	2.5	430	195	2.50	10
V-9298	3.50-10	6PR	17.20 / 437	3.62 / 92	40	2.8	536	243	2.50	10
V-9298	90 / 90-10	4PR	16.38 / 416	3.54 / 90	36	2.5	419	190	2.15	10
V-9298	100 / 90-10	4PR	17.32 / 440	3.98 / 101	36	2.5	494	224	2.50	10
V-9299	100 / 90-10	4PR	17.32 / 440	3.98 / 101	36	2.5	494	224	2.50	10
V-9299	100 / 90-10	6PR	17.32 / 440	3.98 / 101	43	3.0	567	257	2.50	10
V-9501	120 / 70-12	4PR	18.6 / 473	4.8 / 122	33	2.3	430	195	3.50	12
V-9505	3.50-10	4PR	16.9 / 428	3.5 / 88	36	2.5	430	195	2.50	10
V-9505	3.50-10	6PR	16.9 / 428	3.8 / 88	43	2.5	535	243	2.50	10
V-9525	90 / 90-10	4PR	16.4 / 416	3.5 / 90	36	2.5	419	190	2.15	10
V-9529	2.75-10	4PR	15.8 / 402	2.9 / 74	36	2.5	282	128	1.75	10
V-9538	3.50-10	4PR	17.0 / 432	3.5 / 90	36	2.5	430	195	2.50	10
V-9538	3.50-10	6PR	17.0 / 432	3.5 / 90	43	3.0	535	243	2.50	10
V-9542	3.00-10	4PR	16.3 / 413	3.1 / 80	36	2.5	331	150	2.10	10
V-9542	3.00-10	6PR	16.2 / 413	3.1 / 80	43	3.0	418	190	2.15	10
V-9542	3.50-10	4PR	17.2 / 437	3.6 / 92	36	2.5	430	195	2.50	10
V-9542	3.50-10	6PR	17.2 / 437	3.6 / 92	43	3.0	535	243	2.50	10
V-9542	90 / 90-10	4PR	16.4 / 416	3.5 / 90	36	2.5	418	190	2.15	10
V-9542	90 / 90-10	6PR	16.4 / 416	3.5 / 90	43	3.0	493	224	2.15	10
V-9542	100 / 90-10	4PR	17.3 / 440	4.0 / 101	36	2.5	494	224	2.50	10
V-9542	100 / 90-10	6PR	17.1 / 434	4.0 / 101	43	3.0	565	257	2.50	10
V-9542	120 / 90-10	4PR	18.5 / 470	4.7 / 119	33	2.3	534	243	2.75	10
V-9542	120 / 90-10	6PR	18.5 / 470	4.7 / 119	36	2.5	660	300	2.75	10
V-9542	130 / 90-10	4PR	19.2 / 488	5.1 / 129	32	2.3	617	280	3.00	10
V-9542	130 / 90-10	6PR	19.2 / 488	5.0 / 129	36	2.5	737	335	3.00	10
V-9542	130 / 70-13	6PR	20.4 / 518	5.2 / 132	40	2.8	600	150	3.50	13
V-9546	110 / 90-13	6PR	20.6 / 522	4.1 / 104	33	2.3	494	272	2.50	13
V-9548	100 / 90-10	6PR	17.3 / 440	3.9 / 99	43	3.0	565	257	2.50	10
V-9552	3.50-10	4PR	16.9 / 430	3.6 / 91	36	2.5	430	150	2.50	10
V-9552	3.50-10	6PR	16.9 / 430	3.6 / 91	43	3.0	535	195	2.50	10
V-9553	3.50-10	4PR	17.2 / 436	3.7 / 95	36	2.5	430	243	2.50	10
V-9553	3.50-10	6PR	17.2 / 436	3.7 / 95	43	3.0	535	195	2.50	10
V-9556	3.00-10	4PR	16.26 / 413	3.15 / 80	36	2.5	331	150	2.10	10
V-9556	3.00-10	6PR	16.26 / 413	3.15 / 80	43	3.0	419	190	2.10	10
V-9556	3.50-10	4PR	17.20 / 437	3.62 / 92	36	2.5	430	195	2.50	10
V-9556	3.50-10	6PR	17.20 / 437	3.62 / 92	40	2.8	536	243	2.50	10
V-9558	3.00-10	4PR	16.0 / 406	3.1 / 80	36	2.5	330	243	2.10	10
V-9576	3.50-10	4PR	17.2 / 437	3.6 / 92	36	2.5	429	195	2.50	10

Scooter Tire

PATTERN	SIZE	P.R	O.D	S.W	INFLATION		MAXLOAD		R.W.INCHES	
		PLY	In / mm	In / mm	P.S.I	BAR	LBS	KGS	Width	Inches
V-9576	3.50-10	6PR	17.2 / 437	3.6 / 92	43	3.0	535	243	2.50	10
V-9578	4.00-10	4PR	18.0 / 456	4.1 / 105	36	2.5	550	250	3.00	10
V-9596	140 / 70-12	4PR	19.7 / 501	5.5 / 139	33	2.3	550	250	3.75	12
V-9597	130 / 60-13	4PR	19.1 / 486	5.1 / 129	33	2.3	454	206	3.50	13
V-9597	140 / 60-13	4PR	19.6 / 498	5.5 / 139	33	2.3	505	230	3.75	13
V-9611	3.00-10	4PR	16.3 / 413	3.1 / 80	36	2.5	331	150	2.10	10
V-9611	3.00-10	6PR	16.3 / 413	3.1 / 80	43	3.0	418	190	2.15	10
V-9612	3.50-10	4PR	17.2 / 437	3.6 / 92	36	2.5	429	195	2.50	10
V-9612	3.50-10	6PR	17.2 / 437	3.6 / 92	43	3.0	535	243	2.50	10
V-9617	3.00-10	4PR	16.3 / 413	3.1 / 80	36	2.5	330	150	2.15	10
V-9617	3.00-10	6PR	16.3 / 413	3.1 / 80	43	3.0	418	190	2.15	10
V-9617	90 / 90-10	4PR	16.4 / 416	3.6 / 90	36	2.5	418	190	2.15	10
V-9617	90 / 90-10	6PR	16.4 / 416	3.6 / 90	43	3.0	493	224	2.15	10
V-9617	100 / 90-10	4PR	17.1 / 434	4.0 / 101	36	2.5	493	224	2.50	10
V-9617	100 / 90-10	6PR	17.1 / 434	4.0 / 101	43	3.0	565	257	2.50	10
V-9618	3.00-10	4PR	16.1 / 410	3.3 / 83	36	2.5	330	150	2.10	10
V-9618	3.50-10	4PR	17.2 / 437	3.6 / 92	36	2.5	430	195	2.50	10
V-9618	90 / 90-10	4PR	16.4 / 416	3.5 / 90	36	2.5	418	190	2.15	10
V-9622	90 / 90-10	4PR	16.4 / 416	3.6 / 90	36	2.5	418	190	2.15	10
V-9622	90 / 90-10	6PR	16.4 / 416	3.6 / 90	43	3.0	493	224	2.15	10
V-9625	100 / 90-10	4PR	17.1 / 434	4.0 / 101	36	2.5	493	224	2.50	10
V-9625	100 / 90-10	6PR	17.1 / 434	4.0 / 101	43	3.0	565	257	2.50	10
V-9639	3.50-10	4PR	17.2 / 437	3.6 / 92	36	2.5	429	195	2.50	10
V-9639	3.50-10	6PR	17.2 / 437	3.6 / 92	43	3.0	535	243	2.50	10
V-9666	3.50-10	4PR	17.2 / 437	3.6 / 92	36	2.5	535	195	2.50	10
V-9666	3.50-10	6PR	17.2 / 437	3.6 / 92	43	3.0	535	243	2.50	10
V-9888	90 / 90-10	4PR	16.4 / 416	3.5 / 90	36	2.5	418	190	2.15	10
V-9888	90 / 90-10	6PR	16.4 / 416	3.5 / 90	43	3.0	493	224	2.15	10
V-9888	100 / 90-10	4PR	17.1 / 434	4.0 / 101	36	2.5	493	224	2.50	10
V-9888	100 / 90-10	6PR	17.1 / 434	4.0 / 101	43	3.0	535	243	2.50	10
V-9906	130 / 70-12	4PR	19.2 / 487	5.1 / 129	33	2.3	493	224	3.50	12
V-9906	130 / 70-12	6PR	19.2 / 487	5.1 / 129	40	2.8	583	265	3.50	12
V-9910	90 / 90-10	4PR	16.4 / 416	3.5 / 90	36	2.5	418	190	2.15	10
V-9910	100 / 90-10	4PR	17.3 / 440	4.0 / 101	36	2.5	494	224	2.50	10
V-9912	3.50-10	4PR	16.9 / 430	3.6 / 91	36	2.5	430	195	2.50	10
V-9912	3.50-10	6PR	16.9 / 430	3.6 / 91	43	3.0	535	195	2.50	10
V-9913	3.50-10	4PR	17.2 / 437	3.6 / 92	36	2.5	430	195	2.50	10
V-9920	3.00-10	4PR	16.3 / 413	3.1 / 80	36	2.5	331	150	2.10	10
V-9920	3.50-10	4PR	17.2 / 437	3.6 / 92	36	2.5	430	195	2.50	10
V-9920	90 / 90-10	4PR	16.4 / 416	3.5 / 90	36	2.5	418	190	2.15	10
V-9920	100 / 90-10	4PR	17.3 / 440	4.0 / 101	36	2.5	494	224	2.50	10
V-9920	110 / 80-12	6PR	19.3 / 491	4.4 / 112	40	2.8	566	243	3.00	12
V-9920	120 / 70-12	6PR	19.0 / 483	4.7 / 119	40	2.8	519	257	3.50	12
V-9920	130 / 70-12	6PR	19.1 / 485	5.1 / 129	40	2.8	583	236	3.50	12
V-9937	3.00-10	4PR	16.3 / 413	3.1 / 80	36	2.5	330	150	2.10	10
V-9937	3.50-10	4PR	17.2 / 437	3.6 / 92	36	2.5	430	195	2.50	10
V-9937	90 / 90-10	4PR	16.5 / 420	3.5 / 89	36	2.5	418	265	2.15	10
V-9937	90 / 90-10	6PR	16.5 / 420	3.5 / 89	43	3.0	493	190	2.15	10
V-9937	100 / 80-10	4PR	16.2 / 412	4.0 / 102	36	2.5	418	224	2.50	10
V-9937	100 / 80-10	6PR	16.2 / 412	4.0 / 102	43	3.0	520	190	2.50	10
V-9937	100 / 90-10	4PR	17.1 / 434	4.0 / 101	36	2.5	494	224	2.50	10
V-9945	3.00-10	4PR	16.0 / 406	3.1 / 80	36	2.5	330	236	2.10	10
V-9945	3.00-10	6PR	16.0 / 406	3.1 / 80	40	2.8	420	150	2.10	10
V-9945	3.00-10	8PR	16.0 / 406	3.1 / 80	40	2.8	420	190	2.10	10
V-9945	3.50-10	4PR	17.0 / 431	3.6 / 92	36	2.5	430	190	2.50	10
V-9945	3.50-10	6PR	17.0 / 431	3.6 / 92	43	3.0	535	195	2.50	10
V-9945	3.50-10	8PR	17.0 / 431	3.6 / 92	43	3.0	535	243	2.50	10
V-9945	90 / 90-10	4PR	16.5 / 418	3.5 / 89	36	2.5	418	243	2.15	10
V-9945	90 / 90-10	6PR	16.5 / 418	3.5 / 89	43	3.0	493	190	2.15	10
V-9945	90 / 90-10	8PR	16.5 / 418	3.5 / 89	43	3.0	493	224	2.15	10
V-9945	100 / 90-10	6PR	17.3 / 439	4.0 / 101	43	3.0	565	224	2.50	10
V-9945	100 / 90-10	8PR	17.3 / 439	4.0 / 101	43	3.0	565	257	2.50	10
V-9956	3.00-10	4PR	16.3 / 413	3.1 / 80	36	2.5	331	150	2.10	10
V-9956	3.50-10	4PR	17.2 / 437	3.6 / 92	36	2.5	430	195	2.50	10
V-9956	3.50-10	4PR	17.1 / 435	3.7 / 93	36	2.5	430	257	2.50	10
V-9956	3.50-10	6PR	17.1 / 435	3.7 / 93	43	3.0	535	195	2.50	10
V-9957	100 / 90-10	6PR	17.3 / 440	3.9 / 99	43	3.0	565	243	2.50	10
V-9967	120 / 90-10	4PR	18.5 / 470	4.7 / 119	25	1.8	506	230	2.75	10
V-9967	120 / 90-10	6PR	18.5 / 470	4.7 / 119	36	2.5	660	300	2.75	10
V-9967	130 / 90-10	4PR	19.2 / 488	5.1 / 129	25	1.8	565	257	3.00	10

Scooter Tire

PATTERN	SIZE	P.R	O.D	S.W	INFLATION		MAXLOAD		R.W.INCHES	
		PLY	In / mm	In / mm	P.S.I	BAR	LBS	KGS	Width	Inches
V-9967	130 / 90-10	6PR	19.2 / 488	5.1 / 129	36	2.5	737	335	3.00	10
V-9968	3.00-10	4PR	16.1 / 408	3.2 / 82	36	2.5	330	257	2.10	10
V-9973	100 / 80-10	4PR	16.3 / 414	4.0 / 101	32	2.3	494	224	2.50	10
V-9973	100 / 80-10	6PR	16.2 / 412	4.0 / 102	43	3.0	520	236	2.50	10
V-9973	100 / 90-10	6PR	17.3 / 440	3.9 / 99	43	3.0	565	190	2.50	10
V-9985	100 / 90-10	4PR	17.3 / 440	4.0 / 101	36	2.5	494	224	2.50	10
V-9986	3.00-10	4PR	16.1 / 408	3.3 / 83	36	2.5	330	243	2.10	10
V-9989	3.50-10	4PR	17.2 / 437	3.6 / 92	36	2.5	430	195	2.50	10
V-9989	90 / 90-10	4PR	16.4 / 416	3.5 / 90	36	2.5	418	190	2.15	10
V-9989	100 / 90-10	4PR	17.3 / 440	4.0 / 101	36	2.5	494	224	2.50	10
V-9989	110 / 90-10	4PR	17.8 / 452	4.3 / 109	36	2.5	565	257	2.50	10
V-9990	3.50-10	4PR	17.2 / 437	3.6 / 92	36	2.5	430	195	2.50	10
V-9995	120 / 70-10	4PR	16.6 / 422	4.8 / 122	33	2.3	396	180	3.50	10
V-9995	120 / 70-10	6PR	16.6 / 422	4.8 / 122	40	2.8	466	212	3.50	10
V-9999	90 / 90-10	4PR	16.4 / 416	3.5 / 90	36	2.5	418	190	2.15	10
V-9999	100 / 90-10	4PR	17.3 / 440	4.0 / 101	36	2.5	494	224	2.50	10
KT-903	4.00-8	4PR	15.94 / 405	4.13 / 105	36	2.5	480	218	2.50	8
KT-903	4.00-8	6PR	15.94 / 405	4.13 / 105	40	2.8	600	272	2.50	8
V-9972	100 / 90-10	4PR	17.3 / 440	4.0 / 101	36	2.5	494	224	2.50	10
V-9973	3.00-10	4PR	16.0 / 406	3.1 / 80	36	2.5	330	150	2.10	10
V-9973	3.00-10	6PR	16.0 / 406	3.1 / 80	36	2.5	330	150	2.10	10
V-9973	3.50-10	4PR	16.9 / 428	3.5 / 90	36	2.5	430	150	2.50	10
V-9973	3.50-10	6PR	16.9 / 428	3.5 / 90	43	3.0	535	195	2.50	10
V-9973	90 / 90-10	4PR	16.6 / 422	3.5 / 89	36	2.5	418	243	2.15	10

Off Road Tire

PATTERN	SIZE	P.R	O.D	S.W	INFLATION		MAXLOAD		R.W.INCHES	
		PLY	In / mm	In / mm	P.S.I	BAR	LBS	KGS	Width	Inches
V-9962	2.75-17	4PR	23.43 / 595	2.87 / 73	32	2.3	320	145	1.85	17
V-9962	2.75-17	6PR	23.43 / 595	2.87 / 73	40	2.8	386	175	1.85	17
V-9963	2.75-19	4PR	25.39 / 645	3.31 / 84	32	2.3	365	165	1.85	19
V-9965	100/100-18	4PR	25.87 / 657	4.53 / 115	33	2.3	535	243	2.50	18
V-9966	2.75-17	4PR	23.43 / 595	2.95 / 75	33	2.3	320	145	1.85	17
V-9966	2.75-17	6PR	23.43 / 595	2.95 / 75	40	2.8	386	175	1.85	17
V-9966	3.00-17	4PR	24.02 / 610	3.15 / 80	33	2.3	365	165	1.85	17
V-9966	3.00-17	6PR	24.02 / 610	3.15 / 80	40	2.8	419	190	1.85	17
V-9998	120 / 90-10	4PR	18.50 / 470	4.69 / 119	33	2.3	535	243	2.75	10
V-9998	120 / 90-10	6PR	18.50 / 470	4.69 / 119	36	2.5	660	300	2.75	10
V-9998	130 / 90-10	4PR	19.21 / 488	5.08 / 129	32	2.3	617	280	3.00	10
V-9998	130 / 90-10	6PR	19.21 / 488	5.08 / 129	36	2.5	739	335	3.00	10